

DICALITE® CELLULOSE FILTER AIDS

DATA SHEET Nr. 01: Dicacel 1

SPECIFICATIONS:

MINERALOGICAL	Cellulose Fibre
Impurities	None
Physical Form	Dry powder
Colour	White to Cream
Typical Screen Analysis (ASTM E 11 - 70, done on RO-TAP)	
% on 40 Mesh	5 - 15
% through 100 Mesh	35 - 50
% through 200 Mesh	10 - 20

INHERENT PROPERTIES (NOT PART OF THE PRODUCT SPECIFICATIONS):

Approximate Moisture	5 - 8 %
pH	5.5 - 6.5
Brightness (ISO)	+ 90 %
Non Compressed Bulk Density	30 - 50 g/l
Iron	40 -50 ppm
Copper	max. 10 ppm
Ash	max. 0.3 %

OTHER INFORMATION:

Shipping point	Dicalite Warehouse
Packaging	Paper bags 15 kg net

FOR FURTHER INFORMATION PLEASE CONTACT YOUR LOCAL DICALITE SALES DISTRICT OR OUR TECHNICAL SERVICE REPRESENTATIVE AT TEL. +32-9-250.95.50

Specification Nr.: DC01 Page: 1/1	Date: 05-01-1996 Revised: 1 Updated: 05/01/96	Written by: R. Ysewyn	Reviewed by: Tim Neyt
--------------------------------------	--	-----------------------	-----------------------