

**DICALITE® CELLULOSE FILTER AIDS**

**DATA SHEET Nr. 02: Dicacel 2**

**SPECIFICATIONS:**

MINERALOGICAL .....	Cellulose Fibre
Impurities .....	None
Physical Form .....	Dry powder
Colour .....	White to Cream
Typical Screen Analysis (ASTM E 11 - 70, done on RO-TAP)	
% on 40 Mesh .....	1 - 5
% through 100 Mesh .....	50 - 65
% through 200 Mesh .....	15 - 25

**INHERENT PROPERTIES (NOT PART OF THE PRODUCT SPECIFICATIONS):**

Approximate Moisture .....	5 - 8 %
pH .....	5.5 - 6.5
Brightness (ISO) .....	+ 90 %
Non Compressed Bulk Density .....	110 - 150 g/l
Iron .....	40 -50 ppm
Copper .....	max. 10 ppm
Ash .....	max. 0.3 %

**OTHER INFORMATION:**

Shipping point .....	Dicalite Warehouse
Packaging .....	Paper bags 20 kg net

FOR FURTHER INFORMATION PLEASE CONTACT YOUR LOCAL DICALITE SALES DISTRICT OR  
OUR TECHNICAL SERVICE REPRESENTATIVE AT TEL. +32-9-250.95.50

Specification Nr.: DC02  
Page: 1/1

Date: 18-05-2016  
Revised: 1 Updated: 05/01/96

Written by: SHEQ Mgr.

Reviewed by: SHEQ Mgr.